

TECHNICAL DATA SHEET

Danco 6600 Double Sided Tape

PRODUCT:

DESCRIPTION:

APPLICATIONS:

Danco 6600 Double Sided Tape

White PVC double sided tape

- Permanent bonding to most substrates including metal, wood, glass, cement and plastics
- Fixing to decorative trim such as PVC profiles in the furniture industry
- Fastening name plates, luggage tags and labels
- Provides a self-adhesive finish to metal and plastic trim
- Permanent carpet laying

TECHNICAL SPECIFICATIONS:

Carrier Material

Release Liner

Adhesive Type

Total Thickness

Peel Adhesion (PSTC-3)

Shear Strength (PSTC-7)

Heat Resistance

Tensile Strength (machine direction)

Elongation (machine direction)

Service Temperature

Colour Available

STORAGE:

0.05mm unplasticized PVC film

90gsm amber glassine release liner

Acrylic on both sides

0.21mm

2.4 kg/25mm

Over 72 hours, 1kg loading on 25mm x 25mm at 25°C

Over 24 hours, 1kg loading on 25mm x 25mm at 70°C

8 kg/mm²

180%

-20°C to +90°C (short term)

White

Rolls and cartons of tape should be stored in a cool area

and out of direct sunlight

PRODUCT PROPERTIES:

- · High tack that provides quick bonding
- · High peel adhesion
- Good resistance against solvents, chemicals, UV and heat

It is the customer's responsibility to ensure that a particular product with the properties described in this product specification is suitable for use in a specific situation. No warranty, representation or guarantee is given by us regarding the suitability of this product for any particular use. The physical and performance characteristics shown are averages obtained from tests as per PSTC, ASTM and our own internal procedures. A particular roll may vary from these averages. It is suggest that the customer determine the suitability for their own purpose by conducting a rigorous trial process.

Postal PO Box 21806, Henderson, Auckland 0650 Phone 0508 DANCONZ (3262669) Fax (09) 837 3693 Email sales@danco.co.nz

