

DuPont™ Tyvek® FlexWrap™ NF

HIGH PERFORMANCE STRETCHABLE AND FLEXIBLE SELF ADHESIVE FLASHING TAPE



DuPont™ Tyvek® FlexWrap™ NF 152mm x 22.9m

Technical Data

| | |
|------------------------|------------------------------------------------------------------------------------------------|
| Thickness | 1.6 mm |
| Coverage | 3.49 m ² |
| Colour | black / white |
| Rolls per box | 1 |
| Temperature resistance | from - 30 °C till + 80 °C (temporary 100 °C) |
| Elongation | ca. 160 % (2.6 x of the original length) |
| Processing temperature | > -4°C |
| UV resistance | 4 months |
| Storage | 2 years in the initial packaging, in a clean and dry environment, between 5 °C and 25 °C |

BENEFITS

- Helps to facilitate the creation of airtight and watertight seals around windows, door sills, chimney breasts, pipe penetrations and any custom shapes
- Easy to install - no need for additional fasteners
- Designed to ensure continuity, compatibility and integrity with all DuPont™ Tyvek® Building Envelope Solutions products, as well as other non-wovens and laminated membranes at penetrations



DuPont™ Tyvek® FlexWrap™ NF is a stretchable and flexible tape made up of 3 components: a crimped DuPont™ Tyvek® FlexWrap™ NF top sheet providing a watertight layer, the butyl mass as an adhesion layer and a paper release liner. It provides excellent watertight adhesion to all DuPont™ Tyvek® Building Envelope Solutions products around non-straight penetrations, such as dormers, door sills, chimney breasts, pipe penetrations and any custom shapes.

DuPont™ Tyvek® FlexWrap™ NF

INSTALLATION GUIDELINES

A Installation around pipes



Surface preparation

The surface must be free from dirt, moisture, ice, grease and other materials which could reduce the adhesion. DuPont™ Tyvek® FlexWrap™ NF is to be installed when dry and at temperatures above -4°C.



Installation

- Properly position DuPont™ Tyvek® FlexWrap™ NF around the surface to seal.
- Minimize wrinkles and bubbles by smoothing the surface and by repositioning as necessary.
- Apply pressure by hand along the entire surface to achieve a good bond to the substrate. (After pressure has been applied repositioning will be difficult.)
- After completion of the installation DuPont™ Tyvek® FlexWrap™ NF has to be covered within 4 months with the appropriate building materials.
- DuPont™ Tyvek® FlexWrap™ NF can be used around pipes or around windows - refer photos



B Installation around windows



For more information about DuPont™ Tyvek® Building Envelope Solutions, please visit us at pinkbatts.co.nz/duPont

| Description | Product Code | Roll size |
|-------------------------------------|--------------|---------------|
| DuPont™ Tyvek® FlexWrap™ NF - 152mm | 701200 | 152mm x 22.9m |
| DuPont™ Tyvek® FlexWrap™ NF - 228mm | 701201 | 228mm x 22.9m |

The colour PINK and Pink® are registered trademarks of Owens Corning used under license by Tasman Insulation New Zealand Ltd (Tasman). Batts® is the registered trademark of Tasman Insulation. This document supersedes all previous versions and may have been superseded; is a guide only and the purchaser should ascertain the suitability of this product for the end-use situation intended and when used in conjunction with other products; and is provided without prejudice to Tasman standard terms of sale. Tasman retains the right to change specifications without prior notice. Refer to pinkbatts.co.nz or consult Tasman for further information. Do not use this product for any application not detailed in this document. All claims about this product are subject to any variation caused by normal manufacturing process and tolerances. The liability of Tasman and its employees and agents for any errors or omissions in this document or otherwise in relation to the product is limited to the fullest extent permitted by law. Except where the consumer acquires the goods for the purposes of a business, any rights a consumer may have under the Consumer Guarantees Act are not affected.

Copyright © 2017 DuPont. The DuPont Oval Logo, DuPont™, and Tyvek® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved. K-16156 5/17