DANCO®
SPECIALTY ADHESIVE TAPES

TECHNICAL DATA SHEET
Danco 75 Series Foam

PRODUCT:	Danco 75 Series Foam
DESCRIPTION:	Closed cell PVC / nitrile foam
APPLICATIONS:	• Ideal for sealing irregular surfaces where air or moisture seal is required

TECHNICAL SPECIFICATIONS:

Backing Material	Closed cell PVC / nitrile foam
Adhesive Type	Acrylic
Density *(ASTM D-1667)*	64 - 112 kg/m³
Compression Deflection *(ASTM D1050-85)*	14 - 35 kPa
Compression Set	25% loss from original height
Water Absorption	10% by volume
90° Peel Adhesion	411 N/m
Elongation *(ASTM D412-83)*	100%
Thermal Conductivity *(ASTM C518)*	0.031 kcal/(m.h.°C)
Service Temperature	-29°C to +104°C
Application Temperature	+4°C to +52°C
Colour Available	Black

THICKNESSES:	3.0mm / 6.0mm / 9.0mm
STORAGE:	Cartons should be sealed and stored away from direct sunlight at temperatures between 15°C to 30°C

PRODUCT PROPERTIES:

• Good resistance to fungi, weather and oxidation

• Completely seals out air, moisture and light when compressed at least 30%

• Dimensionally stable; will not ooze, drip or run

• Conformable to rough surfaces to ensure a positive seal

• Remains flexible at a wide range of operating temperatures

• Good resistance to most chemicals

• RoHS compliant

DANCO®
SPECIALTY ADHESIVE TAPES

Holding New Zealand together since 1962
www.danco.co.nz