



SPECIALTY ADHESIVE TAPES

TECHNICAL DATA SHEET

Danco 820 & Danco 822 Flashtape

PRODUCT:

Danco 820 & Danco 822 Flashtape

DESCRIPTION:

Self adhesive, aluminium faced, bitumen backed sealing tape

APPLICATIONS:

- A self adhesive sealing strip that bonds instantly to provide watertight seal in all climates
- Bonds to most building materials including brick, slates, concrete roof tiles, glass, roofing felt, rigid plastics, etc
- A wide variety of original construction and maintenance situations including repairing lead flashing, sealing valley gutters, mending leaks in drain pipes and guttering, greenhouse repairs, protecting glazing bars, protecting insulation for pipes and tanks, repairing roofing felt joints on flat roofs.

TECHNICAL SPECIFICATIONS:**Physical Form**

Resin modified bituminous mastic. Upper surface protected by aluminium facing. Adhesive surface protected by a removable release liner.

Chemical Type

Resin modified bituminous mass

Aluminium Foil Thickness

0.05mm

Adhesive Thickness

1.3mm approximately

Solids Content

100%

Weight

1.6 kg/m²

Tensile Strength

1.6 N/mm²

Application Temperature

+5°C to +30°C

Service Temperature

-10°C to +100°C

Colour Available

820 bright finish / 822 Grey lead-like finish

STORAGE:

Rolls and cartons of tape should be stored under dry conditions at temperatures between 5°C to 30°C

PRODUCT PROPERTIES:

- Easily applied using hand pressure only, quick and easy application
- No special equipment required for cutting, forming or fixing
- Superior high temperature performance
- Bonds to wide variety of building materials
- Provides lasting protection in all climates
- Safe in application, storage and transport
- Will not accommodate appreciable joint movement

It is the customer's responsibility to ensure that a particular product with the properties described in this product specification is suitable for use in a specific situation. No warranty, representation or guarantee is given by us regarding the suitability of this product for any particular use. The physical and performance characteristics shown are averages obtained from tests as per PSTC, ASTM and our own internal procedures. A particular roll may vary from these averages. It is suggested that the customer determine the suitability for their own purpose by conducting a rigorous trial process.

Postal PO Box 21806, Henderson, Auckland 0650 **Phone** 0508 DANCONZ (3262669) **Fax** (09) 837 3693 **Email** sales@danco.co.nz